

24 Ports 10/100Mbps PoE switch with 2 Gigabit Combo Ports



Features:

- Fully IEEE802.3af/at standard compliant.
- Support PoE power up to 15.4W/30W for each PoE ports.
- Auto detect powered device(PD).
- Safe and reliable power to most of PoE end device.
- 10/100Mbps Supported.

Specification:

The 24 ports PoE Switches fill the gap between unmanaged and fully managed switches. It is designed for growing businesses that want control over their network without the cost and complexity of a full Layer2 management implementation.

This PoE-capable Switch, provides power and data using built-in IEEE 802.3af PoE on all 24 ports. In addition, this switch offers an intuitive Webbased management tool for quick and easy deployment and configuration making it ideal for deploying access points, VoIP phones and IP-based surveillance camera.

Specification parameter:

| | | |
|---------------------------|---|--|
| Ports description | POE port | 1-24port:10/100M Auto-Negotiation RJ45 |
| | Uplink port | GE1、GE2port:10/100/1000M Auto-Negotiation RJ45 GE3、GE4port:1000M SFP Fiber slot |
| POE power | MAX POE output | 30W |
| | Total power consumption | 250W、450W |
| | POE port priority | Support |
| LED indicators | PWR(Power indicator light)、 POE MAX(Power early warning lamp)、 POE(POE indicator)、 Link/Act(Link / activity indicator) | |
| Processing types | Store and forward | |
| Transmission model | IEEE802.3X full-duplex and Backpressure half-duplex | |
| Performance specification | Backplane bandwidth | 8.8Gbps |
| | Packet forwarding rate | 6.5Mpps |
| | MAC address | 8k |
| Network standard | IEEE802.3i 10 BASE-T IEEE802.3u 100 BASE-TX IEEE802.3ab 1000 BASE-T IEEE802.3x Flow Control IEEE802.3af Power over Ethernet IEEE802.3at Power over Ethernet IEEE802.3az EEE | |
| Input volatage | AC 100~240V 50/60Hz | |
| Dimension | 440mm(L) * 285mm(W) *44mm(H) | |
| Cable requirements | UTP cat5 or abover | |
| Environment specification | Operating temperature: -10℃~45℃ , operating humidity: 10%~90% | |
| | Storage temperature: -20℃~70℃ , storage humidity: 5%~95% | |

Application Solution:

